

1AP1	 Maschio BSP Cono 60°	 BSP Male 60° Cone
	Maschio BSP, cono a 60° Norme di riferimento BS 5200 ISO 12 151-6	BSP Male 60° Cone Applicable Standard BS 5200 ISO 12 151-6

	Quantità	codice	hose ID			thread	S1		L	
			[in]	[mm]	size	T	[in]	[mm]	[in]	[mm]
<input type="checkbox"/>	<input type="text"/>	92MG0404	1/4"	6,4	04	G.1/4"X19	0,75	19,00	1,00	25,50
<input type="checkbox"/>	<input type="text"/>	92MG0604	1/4"	6,4	04	G.3/8"X19	0,87	22,00	1,04	26,50
<input type="checkbox"/>	<input type="text"/>	92MG0605	5/16"	8	05	G.3/8"X19	0,87	22,00	1,04	26,50
<input type="checkbox"/>	<input type="text"/>	92MG0606	3/8"	10	06	G.3/8"X19	0,87	22,00	1,04	26,50
<input type="checkbox"/>	<input type="text"/>	92MG0806	3/8"	10	06	G.1/2"X14	1,06	27,00	1,26	32,00
<input type="checkbox"/>	<input type="text"/>	92MG0608	1/2"	12	08	G.3/8"X19	0,87	22,00	1,10	28,00
<input type="checkbox"/>	<input type="text"/>	92MG0808	1/2"	12	08	G.1/2"X14	1,06	27,00	1,30	33,00
<input type="checkbox"/>	<input type="text"/>	92MG1008	1/2"	12	08	G.5/8"X14	1,18	30,00	1,42	36,00
<input type="checkbox"/>	<input type="text"/>	92MG1010	5/8"	16	10	G.5/8"X14	1,18	30,00	1,46	37,00
<input type="checkbox"/>	<input type="text"/>	92MG1210	5/8"	16	10	G.3/4"X14	1,26	32,00	1,46	37,00
<input type="checkbox"/>	<input type="text"/>	92MG1212	3/4"	19	12	G.3/4"X14	1,26	32,00	1,46	37,00
<input type="checkbox"/>	<input type="text"/>	92MG1612	3/4"	19	12	G.1"X11	1,61	41,00	1,61	41,00
<input type="checkbox"/>	<input type="text"/>	92MG1616	1"	25	16	G.1"X11	1,61	41,00	1,65	42,00
<input type="checkbox"/>	<input type="text"/>	92MG2016	1"	25	16	G.1.1/4"X11	1,97	50,00	1,77	45,00
<input type="checkbox"/>	<input type="text"/>	92MG2020	1.1/4"	32	20	G.1.1/4"X11	1,97	50,00	1,77	45,00
<input type="checkbox"/>	<input type="text"/>	92MG2424	1.1/2"	38	24	G.1.1/2"X11	2,17	55,00	1,93	49,00
<input type="checkbox"/>	<input type="text"/>	92MG3232	2"	51	32	G.2"X11	2,76	70,00	2,15	54,50