

1DL1	 Femmina Serie metrica leggera tipo L	 Metric L-Type Light Series
	<p>Femmina metrica, cono a 24° con O-Ring (serie leggera tipo L)</p> <p>Norme di riferimento ISO 12 151-2</p>	<p>Metric Female 24° Cone O-Ring (L-Type Light Series)</p> <p>Applicable Standard ISO 12 151-2</p>

	Quantità	codice	hose ID			thread	S1		L	
			[in]	[mm]	size	T	[in]	[mm]	[in]	[mm]
+	<input type="text"/>	92DL0603	3/16"	5	03	M.12X1,5 - 06L	0,55	14,00	1,02	26,00
+	<input type="text"/>	92DL0604	1/4"	6,4	04	M.12X1,5 - 06L	0,55	14,00	0,87	22,00
+	<input type="text"/>	92DL0804	1/4"	6,4	04	M.14X1,5 - 08L	0,67	17,00	0,93	23,50
+	<input type="text"/>	92DL1004	1/4"	6,4	04	M.16X1,5 - 10L	0,75	19,00	0,81	20,50
+	<input type="text"/>	92DL1005	5/16"	8	05	M.16X1,5 - 10L	0,75	19,00	1,00	25,50
+	<input type="text"/>	92DL1205	5/16"	8	05	M.18X1,5 - 12L	0,87	22,00	0,93	23,50
+	<input type="text"/>	92DL1006	5/16"	8	05	M.16X1,5 - 10L	0,75	19,00	0,93	23,50
+	<input type="text"/>	92DL1206	3/8"	10	06	M.18X1,5 - 12L	0,87	22,00	1,00	25,50
+	<input type="text"/>	92DL1506	3/8"	10	06	M.22X1,5 - 15L	1,06	27,00	1,06	27,00
+	<input type="text"/>	92DL1208	1/2"	12	08	M.18X1,5 - 12L	0,87	22,00	0,98	25,00
+	<input type="text"/>	92DL1508	1/2"	12	08	M.22X1,5 - 15L	1,06	27,00	1,12	28,50
+	<input type="text"/>	92DL1808	1/2"	12	08	M.26X1,5 - 18L	1,26	32,00	1,18	30,00
+	<input type="text"/>	92DL1810	5/8"	16	10	M.26X1,5 - 18L	1,26	32,00	1,26	32,00
+	<input type="text"/>	92DL2212	3/4"	19	12	M.30X2 - 22L	1,42	36,00	1,32	33,50
+	<input type="text"/>	92DL2812	3/4"	19	12	M.36X2 - 28L	1,61	41,00	1,38	35,00
+	<input type="text"/>	92DL2816	1"	25	16	M.36X2 - 28L	1,61	41,00	1,42	36,00
+	<input type="text"/>	92DL3520	1.1/4"	32	20	M.45X2 - 35L	1,97	50,00	1,38	35,00
+	<input type="text"/>	92DL4224	1.1/2"	38	24	M.52X2 - 42L	2,36	60,00	1,50	38,00