

| | | |
|---|---|---|
| 3BO9 |  3BO9 FEMMINA BSP |  BSP FEMALE |
|  | Femmina BSP 90° cono a 60° con O-Ring Norme di riferimento ISO 12 151-6 | BSP 90° Female 60° Cone O-Ring Applicable Standard ISO 12 151-6 |

| | Quantità | codice | hose ID | | | thread | S1 | | L | |
|--|---|--------|---------|------|------|------------|------|-------|------|--------|
| | | | [in] | [mm] | size | T | [in] | [mm] | [in] | [mm] |
| <input data-bbox="264 890 338 927" type="button" value="+"/> | <input data-bbox="450 890 568 927" type="text" value=""/> | XXXXXX | 3/4" | 19 | 12 | G3/4"X14 | 1,26 | 32,00 | 2,54 | 64,50 |
| <input data-bbox="264 943 338 979" type="button" value="+"/> | <input data-bbox="450 943 568 979" type="text" value=""/> | NEW | 1" | 25 | 16 | G1"X11 | 1,61 | 41,00 | 2,93 | 74,50 |
| <input data-bbox="264 995 338 1032" type="button" value="+"/> | <input data-bbox="450 995 568 1032" type="text" value=""/> | NEW | 1.1/4" | 31 | 20 | G1.1/4"X11 | 1,98 | 50,00 | 3,92 | 99,50 |
| <input data-bbox="264 1048 338 1085" type="button" value="+"/> | <input data-bbox="450 1048 568 1085" type="text" value=""/> | NEW | 1.1/2" | 38 | 24 | G1.1/2"Z11 | 2,17 | 55,00 | 4,33 | 110,00 |
| <input data-bbox="264 1101 338 1137" type="button" value="+"/> | <input data-bbox="450 1101 568 1137" type="text" value=""/> | NEW | 2" | 51 | 32 | G2"X11 | 2,76 | 70,00 | 5,06 | 128,50 |