

<b>ANCHOR 2SC HP</b>	 <b>TUBO 2SC EN 857</b> <b>SAE 100 R16 Hp</b>	 <b>Braided Hose 2SC EN 857</b> <b>SAE 100 R16 HIGH-PRESSURE</b>
	<p><b>Norme di riferimento:</b> Eccede EN 857 2SC Eccede SAE J517 100 R16 .....</p> <p><b>Applicazioni:</b> Linee idrauliche ad alta pressione</p> <p><b>Sottostrato:</b> Gomma sintetica resistente agli oli</p> <p><b>Rinforzo:</b> 2 trecce d'acciaio ad alta resistenza</p> <p><b>Copertura:</b> Gomma sintetica nera resistente agli oli, e agli agenti atmosferici</p> <p><b>Temperatura di esercizio:</b> Olii idraulici: da -40°C a 100°C, Acqua: da 0°C a 70°C, Aria: fino a 70°C</p>	<p><b>Applicable Standard:</b> Exceeds EN 857 2SC Exceeds SAE J517 100 R16</p> <p><b>Application:</b> High pressure hydraulic</p> <p><b>Liner:</b> Oil resistant synthetic rubber</p> <p><b>Reinforcement:</b> Two braids of high tensile steel wire</p> <p><b>Cover:</b> Oil and weather resistant black synthetic rubber</p> <p><b>Operating Temperature:</b> hydraulics Oils from -40°C to 100°C (from -40°F to 212°F) Water: from 0°C to 70°C (from 32°F to 158°F) Air: up to 70°C (up to 158°F)</p>

	Quantità	codice	ID			OD		WP		BP		MBR		TW		NOTE
			[in]	[mm]	size	[in]	[mm]	[psi]	[bar]	[psi]	[bar]	[in]	[mm]	[lb/ft]	[Kg/mt]	
<input data-bbox="241 1018 309 1050" type="button" value="+"/>	<input data-bbox="353 1018 474 1050" type="text" value=""/>	702SC04HP	1/4"	6,4	04	0,559	14,2	6525	450	26105	1800	2,95	75	0,192	0,286	
<input data-bbox="241 1070 309 1102" type="button" value="+"/>	<input data-bbox="353 1070 474 1102" type="text" value=""/>	702SC05HP	5/16"	7,9	05	0,630	16,0	6090	420	24365	1680	3,35	85	0,222	0,330	
<input data-bbox="241 1123 309 1155" type="button" value="+"/>	<input data-bbox="353 1123 474 1155" type="text" value=""/>	702SC06HP	3/8"	9,5	06	0,720	18,3	5365	370	21465	1480	3,54	90	0,282	0,419	
<input data-bbox="241 1176 309 1208" type="button" value="+"/>	<input data-bbox="353 1176 474 1208" type="text" value=""/>	702SC08HP	1/2"	12,7	08	0,846	21,5	4785	330	19140	1320	5,12	130	0,370	0,551	
<input data-bbox="241 1228 309 1260" type="button" value="+"/>	<input data-bbox="353 1228 474 1260" type="text" value=""/>	702SC10HP	5/8"	15,9	10	0,972	24,7	4060	280	16240	1120	6,69	170	0,440	0,655	
<input data-bbox="241 1281 309 1313" type="button" value="+"/>	<input data-bbox="353 1281 474 1313" type="text" value=""/>	702SC12HP	3/4"	19	12	1,126	28,6	3770	260	15080	1040	7,87	200	0,574	0,854	
<input data-bbox="241 1334 309 1366" type="button" value="+"/>	<input data-bbox="353 1334 474 1366" type="text" value=""/>	702SC16HP	1"	25,4	16	1,441	36,6	2900	200	11600	800	9,84	250	0,833	1,239	