

ANCHOR 4SP	 Tubi 4SP EN 856	 Spiral Hose 4SP EN 856
	<p>Norme di riferimento: EN 856 4SP</p> <p>Applicazioni: Linee idrauliche ad alta pressione</p> <p>Sottostrato: Gomma sintetica resistente agli olii</p> <p>Rinforzo: Quattro spirali di filo d'acciaio con elevata resistenza</p> <p>Copertura: Gomma sintetica nera resistente agli olii ed alle condizioni atmosferiche</p> <p>Temperatura di esercizio: Olii idraulici da -40°C a 100°C (da -40°F a 212°F) Acqua: da 0°C a 70°C (da 32°F a 158°F) Aria: fino a 70°C (fino a 158°F)</p>	<p>Applicable Standard: EN 856 4SP</p> <p>Application: High pressure hydraulic lines</p> <p>Liner: Oil resistant synthetic rubber</p> <p>Reinforcement: Four spirals of high tensile steel wire</p> <p>Cover: Oil and weather resistant black synthetic rubber</p> <p>.....</p> <p>Operating Temperature: Hydraulics Oils from -40°C to 100°C (from -40°F to 212°F) Water: from 0°C to 70°C (from 32°F to 158°F) Air: up to 70°C (up to 158°F)</p>

			ID			OD		WP		BP		MBR		TW		
	Quantità	codice	[in]	[mm]	size	[in]	[mm]	[psi]	[bar]	[psi]	[bar]	[in]	[mm]	[lb/ft]	[Kg/mt]	NOTE
<input data-bbox="235 981 302 1029" type="button" value="+"/>	<input data-bbox="347 981 481 1029" type="text" value=""/>	70SP04	1/4"	6,4	04	0,736	18,7	6525	450	26105	1800	5,91	150	0,400	0,596	
<input data-bbox="235 1034 302 1082" type="button" value="+"/>	<input data-bbox="347 1034 481 1082" type="text" value=""/>	70SP06	3/8"	9,5	06	0,874	22,2	6450	445	25815	1780	7,09	180	0,497	0,739	
<input data-bbox="235 1086 302 1134" type="button" value="+"/>	<input data-bbox="347 1086 481 1134" type="text" value=""/>	70SP08	1/2"	12,7	08	1,000	25,4	6015	415	24075	1660	9,06	230	0,571	0,850	
<input data-bbox="235 1139 302 1187" type="button" value="+"/>	<input data-bbox="347 1139 481 1187" type="text" value=""/>	70SP10	5/8"	15,9	10	1,142	29	5075	350	20305	1400	9,84	250	0,782	1,164	
<input data-bbox="235 1192 302 1240" type="button" value="+"/>	<input data-bbox="347 1192 481 1240" type="text" value=""/>	70SP12	3/4"	19	12	1,299	33	5075	350	20305	1400	11,81	300	1,011	1,505	
<input data-bbox="235 1244 302 1292" type="button" value="+"/>	<input data-bbox="347 1244 481 1292" type="text" value=""/>	70SP16	1"	25,4	16	1,610	40,9	4060	280	16240	1120	13,39	340	1,263	1,880	
<input data-bbox="235 1297 302 1345" type="button" value="+"/>	<input data-bbox="347 1297 481 1345" type="text" value=""/>	70SP20	1.1/4"	31,8	20	2,063	52,4	3045	210	12180	840	18,11	460	2,126	3,164	
<input data-bbox="235 1350 302 1398" type="button" value="+"/>	<input data-bbox="347 1350 481 1398" type="text" value=""/>	70SP24	1.1/2"	38,1	24	2,315	58,8	2680	185	10730	740	22,05	560	2,446	3,640	
<input data-bbox="235 1402 302 1450" type="button" value="+"/>	<input data-bbox="347 1402 481 1450" type="text" value=""/>	70SP32	2"	50,8	32	2,811	71,4	2390	165	9570	660	25,98	660	3,178	4,730	