



FAST CARBOPOMP	 TUBO CARBOPOMP 10-NL	 TUBO CARBOPOMP 10-NL
	<p>Compatibile con fluidi in accordo alle norme EN 590:2010</p> <p>Applicazioni: idoneo per adduzione di olii minerali, diesel e benzine ecologiche.</p> <p>Sottostrato: liscio in gomma nera NBR resistente ai prodotti petroliferi con contenuto aromatico non superiore al 50%.</p> <p>Rinforzi: inserzioni di filati sintetici ad alta resistenza.</p> <p>Copertura: in gomma nera nitrilica antistatica (<math>R &lt; 1M \Omega/m</math>) resistente all'abrasione, ai carburanti, agli olii e agli agenti atmosferici.</p> <p>Temperatura: -20 °C +80 °C</p>	<p>Compatible with fluids-according to EN 590:2010.</p> <p>Application: suitable for loading of mineral oils, diesel and unleaded fuel</p> <p>Tube: black, smooth, petroleum products up to 50% aromatic content resistant NBR rubber</p> <p>Reinforcement: high strength synthetic textile yarn</p> <p>Cover: black, abrasion, fuels, oils, and weathering resistant nitrilic antistatic rubber (<math>R &lt; 1M \Omega/m</math>).</p> <p>.....</p> <p>Temperature range: -20 °C +80 °C</p>

	Quantità	codice	ID			OD		WP		BP		MBR		TW		NOTE
			[in]	[mm]	size	[in]	[mm]	[psi]	[bar]	[psi]	[bar]	[in]	[mm]	[lb/ft]	[Kg/mt]	
<input type="checkbox"/>	<input type="text"/>	70CARB05	3/16"	05	3	0.47	12	150	10	450	30	1.57	40	0.09	0,13	
<input type="checkbox"/>	<input type="text"/>	70CARB06	1/4"	06	4	0.51	13	150	10	450	30	1.97	50	0.10	0,14	
<input type="checkbox"/>	<input type="text"/>	70CARB08	5/16"	08	5	0.59	15	150	10	450	30	2.56	65	0.12	0,18	
<input type="checkbox"/>	<input type="text"/>	70CARB10	3/8"	10	6	0.67	17	150	10	450	30	3.15	80	0.14	0,21	
<input type="checkbox"/>	<input type="text"/>	70CARB13	1/2"	13	8	0.78	20	150	10	450	30	4.13	105	0.17	0,26	
<input type="checkbox"/>	<input type="text"/>	70CARB15	19/32"	15	9	0.90	23	150	10	450	30	4.72	120	0.23	0,34	
<input type="checkbox"/>	<input type="text"/>	70CARB16	5/8"	16	10	0.94	24	150	10	450	30	5.12	130	0.21	0,31	
<input type="checkbox"/>	<input type="text"/>	70CARB19	3/4"	19	12	1.06	27	150	10	450	30	5.91	150	0.27	0,40	
<input type="checkbox"/>	<input type="text"/>	70CARB25	1"	25	6	1.37	35	150	10	450	30	7.87	200	0.44	0,66	