

<b>FG-BSP</b>	 <b>CODOLO FEMMINA DIRITTA GAS</b>	 <b>BSP FEMALE 60° FLARE</b>
	<b>CODOLO STANDARD DADO PRESSATO</b> <b>FILETTATURA CILINDRICA</b> <b>OGIVA 60°</b> <b>ZINCATURA TRIVALENTE</b> <b>ACCIAIO AL CARBONIO</b>	<b>STANDARD FLARE PRESSED NUT</b> <b>CYLINDRIC THREADING</b> <b>OGIVE 60°</b> <b>TRIVALENT ZINC COATING</b> <b>CARBON STEEL</b>

	Quantità	codice	hose ID			thread	d		E		cut off C
			[in]	[mm]	size	T	[in]	[mm]	[in]	[mm]	[in]
+	<input type="text"/>	72FG0203	3/16"	4,8	03	1/8-28	0,12	3	0,55	14	0,63
+	<input type="text"/>	72FG0403	3/16"	4,8	03	1/4-19	0,12	3	0,75	19	0,71
+	<input type="text"/>	<a href="#">0416200317</a>	3/16"	4,8	03	3/8-19	0,12	3	0,87	22	0,79
+	<input type="text"/>	72FG0204	1/4"	6,4	04	1/8-28	0,16	4	0,55	14	0,63
+	<input type="text"/>	72FG0404	1/4"	6,4	04	1/4-19	0,16	4	0,75	19	0,71
+	<input type="text"/>	72FG0604	1/4"	6,4	04	3/8-19	0,16	4	0,87	22	0,79
+	<input type="text"/>	72FG0804	1/4"	6,4	04	1/2-14	0,16	4	1,06	27	0,87
+	<input type="text"/>	72FG0405	5/16"	8	05	1/4-19	0,22	5,5	0,75	19	0,71
+	<input type="text"/>	72FG0605	5/16"	8	05	3/8-19	0,22	5,5	0,87	22	0,79
+	<input type="text"/>	72FG0805	5/16"	8	05	1/2-14	0,22	5,5	1,06	27	0,87
+	<input type="text"/>	72FG0406	3/8"	9,5	06	1/4-19	0,28	7	0,75	19	0,71
+	<input type="text"/>	72FG0606	3/8"	9,5	06	3/8-19	0,28	7	0,87	22	0,79
+	<input type="text"/>	72FG0806	3/8"	9,5	06	1/2-14	0,28	7	1,06	27	0,87
+	<input type="text"/>	72FG0806	1/2"	12,7	08	3/8-19	0,35	9	0,87	22	0,79
+	<input type="text"/>	72FG0808	1/2"	12,7	08	1/2-14	0,37	9,5	1,06	27	0,91
+	<input type="text"/>	72FG1008	1/2"	12,7	08	5/8-14	0,37	9,5	1,18	30	0,91
+	<input type="text"/>	72FG1208	1/2"	12,7	08	3/4-14	0,37	9,5	1,26	32	0,87
+	<input type="text"/>	72FG0810	5/8"	16	10	1/2-14	0,47	12	1,06	27	0,91
+	<input type="text"/>	72FG1010	5/8"	16	10	5/8-14	0,47	12	1,18	30	0,87
+	<input type="text"/>	72FG1210	5/8"	16	10	3/4-14	0,47	12	1,26	32	0,87
+	<input type="text"/>	72FG1212	3/4"	19	12	3/4-14	0,59	15	1,26	32	0,91
+	<input type="text"/>	72FG1612	3/4"	19	12	1-11	0,59	15	1,5	38	0,99
+	<input type="text"/>	72FG1616	1"	25,4	16	1-11	0,79	20	1,5	38	1,02