

MJ-JIC	 MASCHIO JIC SV.74°	 JIC MALE 74° FLARE
	CODOLO STANDARD ACCIAIO ZINCATO	STANDARD FLARE GALVANISED STEEL

	Quantità	codice	hose ID			thread	d		E		cut off C	
			[in]	[mm]	size	T	[in]	[mm]	[in]	[mm]	[in]	[mm]
	<input type="text"/>	72MJ0403	3/16"	4,8	03	7/16-20	0,12	3	0,47	12	1,02	26
	<input type="text"/>	72MJ0404	1/4"	6,4	04	7/16-20	0,16	4	0,47	12	1,06	27
	<input type="text"/>	72MJ0504	1/4"	6,4	04	1/2-20	0,16	4	0,55	14	1,06	27
	<input type="text"/>	72MJ0604	1/4"	6,4	04	9/16-18	0,16	4	0,59	15	1,06	27
	<input type="text"/>	72MJ0605	5/16"	8	05	9/16-18	0,22	5,5	0,59	15	1,06	27
	<input type="text"/>	72MJ0606	3/8"	9,5	06	9/16-18	0,28	7	0,59	15	1,06	27
	<input type="text"/>	72MJ0806	3/8"	9,5	06	3/4-16	0,28	7	0,75	19	1,18	30
	<input type="text"/>	72MJ1006	3/8"	9,5	06	7/8-14	0,28	7	0,95	24	1,34	34
	<input type="text"/>	72MJ0808	1/2"	12,7	08	3/4-16	0,37	9,5	0,75	19	1,22	31
	<input type="text"/>	72MJ1008	1/2"	12,7	08	7/8-14	0,37	9,5	0,95	24	1,38	35
	<input type="text"/>	72MJ1208	1/2"	12,7	08	1.1/16-12	0,37	9,5	1,06	27	1,46	37
	<input type="text"/>	72MJ1010	5/8"	16	10	7/8-14	0,47	12	0,95	24	1,38	35
	<input type="text"/>	72MJ1210	5/8"	16	10	1.1/16-12	0,47	12	1,06	27	1,46	37
	<input type="text"/>	72MJ1012	3/4"	19	12	7/8-14	0,59	15	0,95	24	1,42	36
	<input type="text"/>	72MJ1212	3/4"	19	12	1.1/16-12	0,59	15	1,06	27	1,5	38
	<input type="text"/>	72MJ1412	3/4"	19	12	1.3/16-12	0,59	15	1,26	32	1,62	41
	<input type="text"/>	7MJ1612	3/4"	19	12	1.5/16-12	0,59	15	1,34	34	1,65	42
	<input type="text"/>	72MJ1216	1"	25,4	16	1.1/16-12	0,79	20	1,06	27	1,54	39
	<input type="text"/>	72MJ1616	1"	25,4	16	1.5/16-12	0,79	20	1,34	34	1,69	43
	<input type="text"/>	72MJ2016	1"	25,4	16	1.5/8-12	0,79	20	1,65	42	1,81	46
	<input type="text"/>	72MJ2020	1.1/4"	31,8	20	1.5/8-12	1,02	26	1,65	42	1,85	47
	<input type="text"/>	72MJ2420	1.1/4"	31,8	20	1.7/8-12	1,02	26	1,97	50	2,05	52
	<input type="text"/>	72MJ2424	1.1/2"	38,1	24	1.7/8-12	1,26	32	1,97	50	2,05	52
	<input type="text"/>	72MJ3232	2"	50,8	32	2.1/2-12	1,73	44	2,56	65	2,44	62