

MMGG-BSP	 NIPLES DI GIUNZIONE BSP - PROFILO DIN	 BSP NIPLES - DIN PROFILE
	Nipples di giunzione BSP	BSP junction nipple

	Quantità	codice	thread		L		E		Press. Max		NOTE
			T	T1	[in]	[mm]	[in]	[mm]	[psi]	[bar]	
+	<input type="text"/>	74MMGG0202	1/8-28	1/8-28	0,99	25	0,55	14	6164	425	-
+	<input type="text"/>	74MMGG0404	1/4-19	1/4-19	1,26	32	0,75	19	6164	425	-
+	<input type="text"/>	74MMGG0606	3/8-19	3/8-19	1,38	35	0,87	22	5801	400	-
+	<input type="text"/>	74MMGG0808	1/2-14	1/2-14	1,58	40	1,06	27	5076	350	-
+	<input type="text"/>	74MMGG1010	5/8-14	5/8-14	1,65	42	1,18	30	4351	300	-
+	<input type="text"/>	74MMGG1212	3/4-14	3/4-14	1,79	45,5	1,26	32	3626	250	-
+	<input type="text"/>	74MMGG1616	1-11	1-11	2,07	52,5	1,62	41	3626	250	-
+	<input type="text"/>	74MMGG2020	1.1/4-11	1.1/4-11	2,27	57,5	1,97	50	2901	200	-
+	<input type="text"/>	74MMGG2424	1.1/2-11	1.1/2-11	2,36	60	2,17	55	2538	175	-
+	<input type="text"/>	74MMGG3232	2-11	2-11	2,8	71	2,76	70	2175	150	-
+	<input type="text"/>	74MMGG3838	2.1/2-11	2.1/2-11	2,56	65	3,35	85	2175	150	-
+	<input type="text"/>	74MMGG4848	3-11	3-11	2,56	65	3,94	100	1450	100	-