

MN-NPTF	 CODOLO MASCHIO NPTF	 NPTF MALE 60° FLARE
	CODOLO STANDARD FILETTATURA CONICA OGIVA 60° ZINCATURA TRIVALENTE ACCIAIO AL CARBONIO	STANDARD FLARE CONIC THREADING OGIVE 60° TRIVALENT ZINC COATING CARBON STEEL

	Quantità	codice	hose ID			thread	d		E		cut off C
			[in]	[mm]	size	T	[in]	[mm]	[in]	[mm]	[in]
+	<input type="text"/>	72MN0203	3/16"	4,8	03	1/8-27	0,12	3	0,47	12	0,87
+	<input type="text"/>	72MN0403	3/16"	4,8	03	1/4-18	0,12	3	0,59	15	1,1
+	<input type="text"/>	72MN0204	1/4"	6,4	04	1/8-27	0,16	4	0,47	12	0,87
+	<input type="text"/>	72MN0404	1/4"	6,4	04	1/4-18	0,16	4	0,59	15	1,1
+	<input type="text"/>	72MN0604	1/4"	6,4	04	3/8-18	0,16	4	0,75	19	1,1
+	<input type="text"/>	72MN0405	5/16"	8	05	1/4-18	0,22	5,5	0,59	15	1,1
+	<input type="text"/>	72MN0605	5/16"	8	05	3/8-18	0,22	5,5	0,75	19	1,1
+	<input type="text"/>	72MN0406	3/8"	9,5	06	1/4-18	0,28	7	0,59	15	1,1
+	<input type="text"/>	72MN0606	3/8"	9,5	06	3/8-18	0,28	7	0,75	19	1,1
+	<input type="text"/>	72MN0806	3/8"	9,5	06	1/2-14	0,28	7	0,87	22	1,34
+	<input type="text"/>	72MN0608	1/2"	12,7	08	3/8-18	0,37	9,5	0,75	19	1,14
+	<input type="text"/>	72MN0808	1/2"	12,7	08	1/2-14	0,37	9,5	0,87	22	1,38
+	<input type="text"/>	72MN0810	5/8"	16	10	1/2-14	0,47	12	0,87	22	1,38
+	<input type="text"/>	72MN1210	5/8"	16	10	3/4-14	0,47	12	1,06	27	1,42
+	<input type="text"/>	72MN1212	3/4"	19	12	3/4-14	0,59	15	1,06	27	1,46
+	<input type="text"/>	72MN1612	3/4"	19	12	1-11.1/2	0,59	15	1,42	36	1,69
+	<input type="text"/>	72MN1616	1"	25,4	16	1-11.1/2	0,79	20	1,42	36	1,73
+	<input type="text"/>	72MN2016	1"	25,4	16	1.1/4-11.1/2	0,79	20	1,81	46	1,81
+	<input type="text"/>	72MN2020	1.1/4"	31,8	20	1.1/4-11.1/2	1,02	26	1,81	46	1,85
+	<input type="text"/>	72MN2424	1.1/2"	38,1	24	1.1/2-11.1/2	1,26	32	1,97	50	1,93
+	<input type="text"/>	72MN3232	2"	50,8	32	2-11.1/2	1,73	44	2,56	65	2,17