

MS-DKOS	 MASCHIO METRICO SV.24° PESANTE	 METRIC MALE 24° FLARE HEAVY
	CODOLO STANDARD ACCIAIO ZINCATO	STANDARD FLARE GALVANISED STEEL

	Quantità	codice	hose ID			thread	d		E		pipe		cut off C	
			[in]	[mm]	size	T	[in]	[mm]	[in]	[mm]	[in]	[mm]	[in]	[mm]
+		72MS0604	1/4"	6,4	04	M14-1,5 - 06S	0,26	6,7	0,67	17	0,24	6	1,02	26
+		72MS0804	1/4"	6,4	04	M16-1,5 - 08S	0,16	4	0,67	17	0,32	8	1,06	27
+		72MS1004	1/4"	6,4	04	M18-1,5 - 10S	0,16	4	0,75	19	0,39	10	1,06	27
+		72MS1005	5/16"	8	05	M18-1,5 - 10S	0,34	8,5	0,75	19	0,39	10	1,06	27
+		72MS1006	3/8"	9,5	06	M18-1,5 - 10S	0,28	7	0,87	22	0,39	10	1,06	27
+		72MS1205	5/16"	8	05	M20-1,5 - 12S	0,34	8,5	0,87	22	0,47	12	1,14	29
+		72MS1206	3/8"	9,5	06	M20-1,5 - 12S	0,28	7	0,87	22	0,47	12	1,14	29
+		72MS1406	3/8"	9,5	06	M22-1,5 - 14S	0,28	7	0,87	22	0,55	14	1,22	31
+		72MS1408	1/2"	12,7	08	M22-1,5 - 14S	0,28	7	0,87	22	0,55	14	1,22	31
+		72MS1608	1/2"	12,7	08	M24-1,5 - 16S	0,37	9,5	0,95	24	0,63	16	1,26	32
+		72MS2010	5/8"	16	10	M30-2 - 20S	0,47	12	1,18	30	0,79	20	1,34	34
+		72MS2012	3/4"	19	12	M30-2 - 20S	0,59	15	1,18	30	0,79	20	1,38	35
+		72MS2512	3/4"	19	12	M36-2 - 25S	0,59	15	1,42	36	0,99	25	1,5	38
+		72MS2516	1"	25,4	16	M36-2 - 25S	0,79	20	1,42	36	0,99	25	1,54	39
+		72MS3016	1"	25,4	16	M42-2 - 30S	0,79	20	1,81	46	1,18	30	1,65	42
+		72MS3820	1.1/4"	31,8	20	M52-2 - 38S	1,02	26	2,17	55	1,5	38	1,97	50