

NG-BSP	 CODOLO FEMMINA 90° GAS	 BSP FEMALE 60° FLARE 90° ELBOW
	CODOLO STANDARD DADO PRESSATO FILETTATURA CILINDRICA OGIVA 60° ZINCATURA TRIVALENTE ACCIAIO AL CARBONIO	STANDARD FLARE PRESSED NUT CYLINDRIC THREADING OGIVE 60° TRIVALENT ZINC COATING CARBON STEEL

	Quantità	codice	hose ID			thread	d		E		cut off C		drop H	
			[in]	[mm]	size	T	[in]	[mm]	[in]	[mm]	[in]	[mm]	[in]	[mm]
+	<input type="text"/>	72NG0302	3/16"	4,8	03	1/8-28	0,12	3	0,55	14	0,87	22	0,95	24
+	<input type="text"/>	72NG0204	3/16"	4,8	03	1/4-19	0,12	3	0,75	19	0,91	23	1,1	28
+	<input type="text"/>	72NG0404	1/4"	6,4	04	1/4-19	0,16	4	0,75	19	0,99	25	1,1	28
+	<input type="text"/>	72NG0604	1/4"	6,4	04	3/8-19	0,16	4	0,87	22	0,99	25	1,22	31
+	<input type="text"/>	72NG0605	5/16"	8	05	3/8-19	0,22	5,5	0,87	22	1,14	29	1,42	36
+	<input type="text"/>	72NG0606	3/8"	9,5	06	3/8-19	0,28	7	0,87	22	1,3	33	1,38	35
+	<input type="text"/>	72NG0806	3/8"	9,5	06	1/2-14	0,28	7	1,06	27	1,3	33	1,46	37
+	<input type="text"/>	72NG0608	1/2"	12,7	08	3/8-19	0,37	9,5	0,87	22	1,54	39	1,62	41
+	<input type="text"/>	72NG0808	1/2"	12,7	08	1/2-14	0,37	9,5	1,06	27	1,54	39	1,62	41
+	<input type="text"/>	72NG0810	1/2"	12,7	08	5/8-14	0,37	9,5	1,18	30	1,54	39	1,73	44
+	<input type="text"/>	72NG0812	1/2"	12,7	08	3/4-14	0,37	9,5	1,26	32	1,54	39	1,73	44
+	<input type="text"/>	72NG1010	5/8"	16	10	5/8-14	0,47	12	1,18	30	1,77	45	1,93	49
+	<input type="text"/>	72NG1210	5/8"	16	10	3/4-14	0,47	12	1,26	32	1,77	45	2,01	51
+	<input type="text"/>	72NG1212	3/4"	19	12	3/4-14	0,59	15	1,26	32	2,21	56	2,13	54
+	<input type="text"/>	72NG1612	3/4"	19	12	1-11	0,59	15	1,5	38	2,21	56	2,29	58
+	<input type="text"/>	72NG1616	1"	25,4	16	1-11	0,79	20	1,5	38	2,76	70	2,56	65