

NV MASCHIO	 <b>TIPO NV MASCHIO</b>	 <b>MALE NV</b>
	<p>Acciaio ad alto tenore di carbonio</p> <p>Temperature di esercizio: da -25°C a +125°C</p> <p>Norme di riferimento ISO 7241-2</p>	<p>High grade carbon steel</p> <p>Operating Temperatures: from -25°C to +125°C</p> <p>Applicable standard ISO 7241-2</p>

	Quantità	codice	SIZE		FILETTO	B		D		X		WP		FR		NOTE
			[in]	[mm]	[in]	[in]	[mm]	[in]	[mm]	[in]	[mm]	[psi]	[bar]	[l/min]	[GPM]	
<input type="checkbox"/>	<input type="text"/>	75FA0NV04M	1/4"	6,3	F	1,30	33	1/4"	6,3	0,75	19	5000	344,74	15	3,9	
<input type="checkbox"/>	<input type="text"/>	75FA0NV06M	3/8"	10	F	1,54	39	3/8"	10	0,94	24	4500	310,26	50	13,2	
<input type="checkbox"/>	<input type="text"/>	75FA0NV08M	1/2"	12,5	F	1,73	44	1/2"	12,5	1,06	27	4500	310,26	75	19,8	
<input type="checkbox"/>	<input type="text"/>	75FA0NV12M	3/4"	20	F	2,13	54	3/4"	20	1,34	34	4500	310,26	150	39,6	
<input type="checkbox"/>	<input type="text"/>	75FA0NV16M	1"	25	F	2,60	66	1"	25	1,61	41	3625	249,93	230	60,8	
<input type="checkbox"/>	<input type="text"/>	75FA0NV20M	1.1/4"	31,5	F	2,87	73	1.1/4"	31,5	1,97	50	3300	227,53	340	89,8	