

QG-BSP	 CODOLO FEMMINA 45° GAS	 BSP FEMALE 60° FLARE 45° ELBOW
	CODOLO STANDARD DADO PRESSATO FILETTATURA CILINDRICA OGIVA 60° ZINCATURA TRIVALENTE ACCIAIO AL CARBONIO	STANDARD FLARE PRESSED NUT CYLINDRIC THREADING OGIVE 60° TRIVALENT ZINC COATING CARBON STEEL

	Quantità	codice	hose ID			thread	d		E		cut off C		drop H	
			[in]	[mm]	size	T	[in]	[mm]	[in]	[mm]	[in]	[mm]	[in]	[mm]
+	<input type="text"/>	72QG0203	3/16"	4,8	03	1/8-28	0,12	3	0,55	14	1,34	34	0,63	16
+	<input type="text"/>	72QG0403	3/16"	4,8	03	1/4-19	0,12	3	0,75	19	1,46	37	0,67	17
+	<input type="text"/>	72QG0204	1/4"	6,4	04	1/8-28	0,16	4	0,75	19	1,38	35	0,63	16
+	<input type="text"/>	72QG0404	1/4"	6,4	04	1/4-19	0,16	4	0,75	19	1,62	41	0,63	16
+	<input type="text"/>	72QG0604	1/4"	6,4	04	3/8-19	0,16	4	0,87	22	1,69	43	0,79	20
+	<input type="text"/>	72QG0605	5/16"	8	05	3/8-19	0,22	5,5	0,87	22	1,5	38	0,83	21
+	<input type="text"/>	72QG0606	3/8"	9,5	06	3/8-19	0,28	7	0,87	22	1,73	44	0,75	19
+	<input type="text"/>	72QG0806	3/8"	9,5	06	1/2-14	0,28	7	1,06	27	1,62	41	0,87	22
+	<input type="text"/>	72QG0808	1/2"	12,7	08	1/2-14	0,37	9,5	1,06	27	1,97	50	0,91	23
+	<input type="text"/>	72QG1008	1/2"	12,7	08	5/8-14	0,37	9,5	1,18	30	2,56	65	0,95	24
+	<input type="text"/>	72QG1208	1/2"	12,7	08	3/4-14	0,37	9,5	1,26	32	2,13	54	0,99	25
+	<input type="text"/>	72QG1010	5/8"	16	10	5/8-14	0,47	12	1,18	30	2,32	59	1,06	27
+	<input type="text"/>	72QG1210	5/8"	16	10	3/4-14	0,47	12	1,26	32	2,36	60	0,99	25
+	<input type="text"/>	72QG1212	3/4"	19	12	3/4-14	0,59	15	1,26	32	2,76	70	1,1	28
+	<input type="text"/>	72QG1612	3/4"	19	12	1-11	0,59	15	1,5	38	2,96	75	1,18	30
+	<input type="text"/>	72QG1616	1"	25,4	16	1-11	0,79	20	1,5	38	3,31	84	1,38	35