

QG.DSP-BSP	 CODOLO FEMMINA 45° GAS	 BSP FEMALE 60° FLARE 45° ELBOW WITH THRUST WIRE NUT
	CODOLO STANDARD DADO SPINATO FILETTATURA CILINDRICA OGIVA 60° ZINCATURA TRIVALENTE ACCIAIO AL CARBONIO	STANDARD FLARE BARBED NUT CYLINDRIC THREADING OGIVE 60° TRIVALENT ZINC COATING CARBON STEEL

	Quantità	codice	hose ID			thread	d		E		cut off C		drop H		NOTE
			[in]	[mm]	size	T	[in]	[mm]	[in]	[mm]	[in]	[mm]	[in]	[mm]	
+		72QG0403DSP	3/16"	4,8	03	1/4-19	0,12	3	0,75	19	1,38	35	0,67	17	a richiesta
+		72QG0204DSP	1/4"	6,4	04	1/8-28	0,16	4	0,55	14	1,38	35	0,55	14	a richiesta
+		72QG0404DSP	1/4"	6,4	04	1/4-19	0,16	4	0,75	19	1,46	37	0,63	16	a richiesta
+		72QG0604DSP	1/4"	6,4	04	3/8-19	0,16	4	0,87	22	1,54	39	0,71	18	a richiesta
+		72QG0605DSP	5/16"	8	05	3/8-19	0,22	5,5	0,87	22	1,5	38	0,83	21	a richiesta
+		72QG0606DSP	3/8"	9,5	06	3/8-19	0,28	7	0,87	22	1,73	44	0,75	19	a richiesta
+		72QG0806DSP	3/8"	9,5	06	1/2-14	0,28	7	1,06	27	1,77	45	0,79	20	a richiesta
+		72QG0608DSP	1/2"	12,7	08	3/8-19	0,37	9,5	0,87	22	2,01	51	0,87	22	a richiesta
+		72QG0808DSP	1/2"	12,7	08	1/2-14	0,37	9,5	1,06	27	2,05	52	0,91	23	a richiesta
+		72QG1208DSP	1/2"	12,7	08	3/4-14	0,37	9,5	1,26	32	2,21	56	1,06	27	a richiesta
+		72QG1010DSP	5/8"	16	10	5/8-14	0,47	12	1,18	30	2,32	59	0,95	24	a richiesta
+		72QG1212DSP	3/4"	19	12	3/4-14	0,59	15	1,26	32	2,8	71	1,14	29	a richiesta
+		72QG1612DSP	3/4"	19	12	1-11	0,59	15	1,5	38	2,92	74	1,26	32	a richiesta
+		72QG1616DSP	1"	25,4	16	1-11	0,79	20	1,5	38	3,31	84	1,38	35	a richiesta
+		72QG2016	1"	25,4	16	1.1/4-11	0,79	20	1,97	50	3,39	86	1,46	37	
+		72QG2020	1.1/4"	31,8	20	1.1/4-11	1,02	26	1,97	50	4,06	103	1,97	50	
+		72QG2424	1.1/2"	38,1	24	1.1/2-11	1,26	32	2,17	55	4,57	116	2,17	55	
+		72QG3232	2"	50,8	32	2-11	1,73	44	2,76	70	5,63	143	2,76	70	