

QNGG	 NIPLES 45 F. GIR. F. GIR. BSP SV.60	 Nipple 45 F. IBC. F. IBC. BSP SV.60
	Niples di giunzione girevole 45° F/F	45° F/F Turning Junction Nipple

	Quantità	codice	thread		L		H		E		E1		Press.Max		NOTE
			T	T1	[in]	[mm]	[in]	[mm]	[in]	[mm]	[in]	[mm]	[psi]	[bar]	
<input data-bbox="241 917 309 965" type="button" value="+"/>	<input data-bbox="362 917 481 965" type="text"/>	74QQGG0404	1/4"- 19	1/4"- 19	1,69	42,9	0,67	17,1	0,75	19	0,75	19	5076	350	
<input data-bbox="241 970 309 1018" type="button" value="+"/>	<input data-bbox="362 970 481 1018" type="text"/>	74QQGG0606	3/8"-19	3/8"-19	2,11	53,5	0,83	21,0	0,87	22	0,87	22	4351	300	
<input data-bbox="241 1023 309 1070" type="button" value="+"/>	<input data-bbox="362 1023 481 1070" type="text"/>	74QQGG0808	1/2"- 14	1/2"- 14	2,22	56,3	0,94	23,8	1,06	27	1,06	27	3626	250	
<input data-bbox="241 1075 309 1123" type="button" value="+"/>	<input data-bbox="362 1075 481 1123" type="text"/>	74QQGG1212	3/4"- 14	3/4"- 14	2,53	64,2	1,02	25,9	1,26	32	1,26	32	2901	200	
<input data-bbox="241 1128 309 1176" type="button" value="+"/>	<input data-bbox="362 1128 481 1176" type="text"/>	74QQGG1616	1"- 11	1"- 11	3,20	81,1	1,34	33,9	1,50	38	1,50	38	2901	200	