

| | | |
|-----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| QP-DKOS |  FEMMINA 45° METRICA SV.24° PESANTE DKOS |  METRIC FEMALE 24° FLARE HEAVY 45° ELBOW |
|  | CODOLO STANDARD ACCIAIO ZINCATO | STANDARD FLARE GALVANISED STEEL |

| | Quantità | codice | hose ID | | | thread | d | | E | | pipe | | cut off C | | drop H | |
|---|----------|----------|---------|------|------|---------------|------|------|------|------|------|------|-----------|--------|--------|--------|
| | | | [in] | [mm] | size | T | [in] | [mm] | [in] | [mm] | [in] | [mm] | [in] | [mm] | [in] | [in] |
| + | | 72QP0604 | 1/4" | 6,4 | 04 | M14-1,5 - 06S | 0,26 | 6,7 | 0,75 | 19 | 0,24 | 6 | 1,42 | 36 | 0,63 | 16 |
| + | | 72QP0804 | 1/4" | 6,4 | 04 | M16-1,5 - 08S | 0,16 | 4 | 0,75 | 19 | 0,32 | 8 | 1,42 | 36 | 0,59 | 15 |
| + | | 72QP1004 | 1/4" | 6,4 | 04 | M18-1,5 - 10S | 0,16 | 4 | 0,87 | 22 | 0,39 | 10 | 1,58 | 40 | 0,63 | 16 |
| + | | 72QP1005 | 5/16" | 8 | 05 | M18-1,5 - 10S | 0,22 | 5,5 | 0,87 | 22 | 0,39 | 10 | 1,69 | 43 | 0,75 | 19 |
| + | | 72QP1006 | 3/8" | 9,5 | 06 | M18-1,5 - 10S | 0,41 | 10,3 | 0,87 | 22 | 0,39 | 10 | 2,13 | 54 | 0,71 | 18 |
| + | | 72QP1205 | 5/16" | 8 | 05 | M20-1,5 - 12S | 0,22 | 5,5 | 0,95 | 24 | 0,47 | 12 | 1,65 | 42 | 0,75 | 19 |
| + | | 72QP1206 | 3/8" | 9,5 | 06 | M20-1,5 - 12S | 0,28 | 7 | 0,95 | 24 | 0,47 | 12 | 1,54 | 39 | 0,71 | 18 |
| + | | 72QP1406 | 3/8" | 9,5 | 06 | M22-1,5 - 14S | 0,28 | 7 | 1,06 | 27 | 0,55 | 14 | 1,73 | 44 | 0,75 | 19 |
| + | | 72QP1408 | 1/2" | 12,7 | 08 | M22-1,5 - 14S | 0,28 | 7 | 1,06 | 27 | 0,55 | 14 | 1,73 | 44 | 0,75 | 19 |
| + | | 72QP1608 | 1/2" | 12,7 | 08 | M24-1,5 - 16S | 0,37 | 9,5 | 1,18 | 30 | 0,63 | 16 | 1,93 | 49 | 0,79 | 20 |
| + | | 72QP2010 | 5/8" | 16 | 10 | M30-2 - 20S | 0,47 | 12 | 1,42 | 36 | 0,79 | 20 | 2,48 | 63 | 1,06 | 27 |
| + | | 72QP2012 | 3/4" | 19 | 12 | M30-2 - 20S | 0,59 | 15 | 1,42 | 36 | 0,79 | 20 | 2,88 | 73 | 1,18 | 30 |
| + | | 72QP2512 | 3/4" | 19 | 12 | M36-2 - 25S | 0,59 | 15 | 1,81 | 46 | 0,99 | 25 | 2,84 | 72 | 1,26 | 32 |
| + | | 72QP2516 | 1" | 25,4 | 16 | M36-2 - 25S | 0,79 | 20 | 1,81 | 46 | 0,99 | 25 | 3,43 | 87 | 1,58 | 40 |
| + | | 72QP3016 | 1" | 25,4 | 16 | M42-2 - 30S | 0,79 | 20 | 1,97 | 50 | 1,18 | 30 | 3,31 | 84 | 1,38 | 35 |
| + | | 72QP3820 | 1.1/4" | 31,8 | 20 | M52-2 - 38S | 1,02 | 26 | 2,36 | 60 | 1,5 | 38 | 4,41 | 105 | 1,97 | 50 |