




RADIALE DIA 63

Manometro Radiale Dia 63 1
 4" gas Cl.1.6


Bottom Pressure Gauge Dia 63 1
 4" gas Cl.1.6


Manometri per fluidi non corrosivi a temperature tra i -20 +80°C

Movimento amplificatore di precisione in ottone.

Quadrante in alluminio verniciato a forno

Elemento manometrico: - tubo Bourdon in lega di rame per pressioni da -1 a 40 bar. - tubo a spirale in lega di rame per pressioni da 50 a 1000 bar. Saldature in lega di stagno.

Grado di protezione Ip 65.

Sovrappressione ammessa sui manometri standard. -

Statica: 3/4 - Fluttuante: 2/3 del valore di fondo scala del manometro.

Pressure gauges for non-corrosive fluids at temperatures between -20 and +80°C

Precision amplifier movement in brass. Dial in stove-enamelled aluminium

Pressure gauge parts: - Bourdon tube in copper alloy for pressure ratings from -1 to 40 bar. - spiral tube in copper alloy for pressure ratings from 50 to 1000 bar.

Protection degree Ip 65

Overpressure permitted on standard gauges. - Steady:

3/4 - Fluctuating: 2/3 of full scale value of the gauge.

	Quantità	codice	SCALA		A		B		I		NOTE
			[psi]	[bar]	[in]	[mm]	[in]	[mm]	[in]	[mm]	
+	<input type="text"/>	79AR63001	14,5	1	1,18	30	2,99	76	0,14	3,6	
+	<input type="text"/>	79AR63002	36,26	2,5	1,18	30	2,99	76	0,14	3,6	
+	<input type="text"/>	79AR63004	58,01	4	1,18	30	2,99	76	0,14	3,6	
+	<input type="text"/>	79AR63006	87,02	6	1,18	30	2,99	76	0,14	3,6	
+	<input type="text"/>	79AR63010	145	10	1,18	30	2,99	76	0,14	3,6	
+	<input type="text"/>	79AR63016	232,06	16	1,18	30	2,99	76	0,14	3,6	
+	<input type="text"/>	79AR63025	362,59	25	1,18	30	2,99	76	0,14	3,6	
+	<input type="text"/>	79AR63040	580,15	40	1,18	30	2,99	76	0,14	3,6	
+	<input type="text"/>	79AR63060	870,22	60	1,18	30	2,99	76	0,14	3,6	
+	<input type="text"/>	79AR63100	1450	100	1,18	30	2,99	76	0,14	3,6	
+	<input type="text"/>	79AR63160	2320	160	1,18	30	2,99	76	0,14	3,6	
+	<input type="text"/>	79AR63250	3625	250	1,18	30	2,99	76	0,14	3,6	
+	<input type="text"/>	79AR63315	4568	315	1,18	30	2,99	76	0,14	3,6	
+	<input type="text"/>	79AR63400	5801	400	1,18	30	2,99	76	0,14	3,6	
+	<input type="text"/>	79AR63600	8702	600	1,18	30	2,99	76	0,14	3,6	
+	<input type="text"/>	79AR63M10	14503	1000	1,18	30	2,99	76	0,14	3,6	