

<b>XNGGCO</b>	  <b>NIPLES 90 M F GIR. COMPATTO</b>	 <b>Nipple 90 M F IBC. COMPACT</b>
	<b>Adattatore 90° Girevole M/F Compatto</b>	<b>90° M/F Turning Compact Adapter</b>

	Quantità	codice	thread		L		H		E		Press.Max		NOTE
			T	T1	[in]	[ mm ]	[in]	[mm]	[in]	[mm]	[psi]	[bar]	
+	<input type="text"/>	74XNGGCO04	1/4"-19	1/4"-19	1,14	29,0	1,06	27,0	0,75	19	5075	350	
+	<input type="text"/>	74XNGGCO06	3/8"- 19	3/8"- 19	1,34	34,0	1,26	32,0	0,87	22	5075	350	
+	<input type="text"/>	74XNGGCO08	1/2"- 14	1/2"- 14	1,58	40,0	1,46	37,0	1,06	27	5075	350	
+	<input type="text"/>	74XNGGCO12	3/4"- 14	3/4"- 14	1,81	46,0	1,58	40,0	1,26	32	4495	310	
+	<input type="text"/>	74XNGGCO16	1"- 11	1"- 11	2,05	52,0	1,97	50,0	1,50	38	3480	240	
+	<input type="text"/>	74XNGGCO20	1.1/4"- 11	1.1/4"- 11	2,25	57,0	2,05	52,0	1,97	50	2900	200	
+	<input type="text"/>	74XNGGCO24	1.1/2"- 11	1.1/2"- 11	2,52	64,0	2,32	59,0	2,17	55	2030	140	