




XNGH-OR	 NIPLES 90 M.BSP-OR F.GIR.ORFS	 M BSP-OR - F ORFS TURNING 90° NIPPLE
	Nipples 90° M BSP-OR / F Girevole ORFS	BSP-OR Male / ORFS Turning Female 90° Nipple

	Quantità	codice	thread		L		L1		E		Press.Max		NOTE
			T	T1	[in]	[mm]	[in]	[mm]	[in]	[mm]	[psi]	[bar]	
<input type="checkbox"/>	<input type="text"/>	74XNGH0204	1/8"- 27	9/16"-18	1,18	30	1,04	26,5	0,75	19	5076	350	
<input type="checkbox"/>	<input type="text"/>	74XNGH0406	1/4"- 19	11/16"- 16	1,45	37	1,14	29	0,94	22	4569	315	
<input type="checkbox"/>	<input type="text"/>	74XNGH0608	3/8"-19	13/16"- 16	1,49	38	1,49	38	0,94	24	3626	250	
<input type="checkbox"/>	<input type="text"/>	74XNGH0810	1/2"- 14	1"- 14	1,89	48	1,61	41	1,18	30	3626	250	
<input type="checkbox"/>	<input type="text"/>	74XNGH1212	3/4"- 14	1.3/16"- 12	2,02	51,5	1,83	46,5	1,42	36	3626	250	
<input type="checkbox"/>	<input type="text"/>	74XNGH1616	1"- 11	1.7/16"- 12	2,30	58,5	2,10	53,5	1,81	46	2900	200	
<input type="checkbox"/>	<input type="text"/>	74XNGH1616	1.1/4"- 11	1.11/16"- 12	2,38	60,5	2,28	58	1,97	50	2900	200	
<input type="checkbox"/>	<input type="text"/>	74XNGH2424	1.1/2"- 11	2"- 12	2,52	64	2,40	61	2,36	60	2320	160	