




<b>XNHH-ORFS</b>	 <b>NIPLES 90 M.ORFS F. GIR. ORFS</b>	 <b>M ORFS - F ORFS TURNING 90° NIPPLE</b>
	<b>Niples 90° M ORFS / F Girevole ORFS</b>	<b>ORFS Male / ORFS Turning Female 90° Nipple</b>

	Quantità	codice	thread		L		L1		E		Press.Max		NOTE
			T	T1	[in]	[mm]	[in]	[ mm ]	[ in ]	[ mm ]	[psi]	[bar]	
+	<input type="text"/>	74XNHH0404	9/16"- 18	9/16"- 18	0,84	21,5	1,04	26,5	0,75	19	9137	630	
+	<input type="text"/>	74XNHH0606	11/16"- 16	11/16"- 16	0,98	25	1,14	29	0,86	22	9137	630	
+	<input type="text"/>	74XNHH0808	13/16"- 16	13/16"- 16	1,10	28	1,49	38	0,94	24	9137	630	
+	<input type="text"/>	74XNHH1010	1"- 14	1"- 14	1,32	33,5	1,61	41	1,18	30	6091	420	
+	<input type="text"/>	74XNHH1212	1.3/16"-12	1.3/16"-12	1,47	37,5	1,83	46,5	1,42	36	6091	420	
+	<input type="text"/>	74XNHH1616	1.7/16"-12	1.7/16"-12	1,63	41,5	2,10	53,5	1,81	46	6091	420	
+	<input type="text"/>	74XNHH2020	1.11/16"-12	1.11/16"-12	1,75	44,5	2,28	58	1,97	50	4061	280	
+	<input type="text"/>	74XNHH2424	2"-12	2"-12	1,93	49	2,40	61	2,36	60	4061	280	