




<b>XX GH-OR</b>	 <b>NIPLES 90 M.BSP-OR M.ORFS</b>	 <b>M BSP-OR - M ORFS 90° NIPPLE</b>
	<b>Nipples 90° M BSP-OR / M ORFS</b>	<b>BSP-OR Male - ORFS Male 90° Nipple</b>

	Quantità	codice	thread		L		L1		E		Press.Max		NOTE
			T	T1	[in]	[mm]	[in]	[ mm ]	[ in ]	[ mm ]	[psi]	[bar]	
+	<input type="text"/>	74XXGH0404	1/4"-19	9/16"-18	1,38	35	0,84	21,5	0,75	19	4569	315	
+	<input type="text"/>	74XXGH0406	1/4"- 19	11/16"- 16	1,45	37	0,98	25	0,75	19	4569	315	
+	<input type="text"/>	74XXGH0606	3/8"-19	11/16"- 16	1,49	38	0,98	25	0,86	22	3626	250	
+	<input type="text"/>	74XXGH0608	3/8"- 19	13/16"- 16	1,49	38	1,10	28	0,86	22	3626	250	
+	<input type="text"/>	74XXGH0610	3/8"- 19	1"- 14	1,67	42,5	1,32	33,5	0,86	22	3626	250	
+	<input type="text"/>	74XXGH0808	1/2"- 14	13/16"- 16	1,49	38	1,10	28	0,86	22	3626	250	
+	<input type="text"/>	74XXGH0810	1/2"- 14	1"- 14	1,89	48	1,32	33,5	1,06	27	3626	250	
+	<input type="text"/>	74XXGH0812	1/2"- 14	1.3/16"- 12	1,89	48	1,18	30	1,06	27	3626	250	
+	<input type="text"/>	74XXGH1212	3/4"- 14	1.3/16"-12	2,02	51,5	1,24	31,5	1,42	36	3626	250	
+	<input type="text"/>	74XXGH1216	3/4"- 14	1.7/16"- 12	2,26	57,5	1,63	41,5	1,49	36	3626	250	
+	<input type="text"/>	74XXGH1612	1"- 11	1.3/16"- 12	2,30	58,5	1,49	38	1,61	41	2900	200	
+	<input type="text"/>	74XXGH1616	1"- 11	1.7/16"- 12	2,30	58,5	1,63	41,5	1,61	41	2900	200	